

S2-2018 www.safirecctv.com



PRODUCT
SELECTION | **CCTV**
ACCESS CONTROL



safire

Model	5MP PRO			1080p ECO+ (PoC version)		
						
	SF-DM942KIB-5MT	SF-CV022KIB-5MT	SF-DM955ZK-5MT	SF-DM855ZP-5MT	SF-DM935ZP-5MT	SF-CV788ZP-5MT
Image Sensor Type	5 MP High performance CMOS Ultra Low Light			5MP High performance CMOS		
Effective pixel	2592 (H) × 1944 (V)			2560 (H) × 1944 (V)		
Focal length	2.8 mm	2.8 mm	2.8-12 mm MotorZoom	2.8-12 mm AutoFocus MotorZoom		
Field of view	94°	94°				

Model	1080p Ultra Low Light					
						
	SF-DM836KWU-F4N1	SF-DM942KWU-F4N1	SF-CV022KWU-F4N1	SF-DM832ZWU-F4N1	SF-DM855ZWU-F4N1	SF-CV788ZKWU-F4N1
Image Sensor Type	2MP High performace CMOS Ultra Low Light					
Effective pixel	1920 (H) × 1080 (V)					
Focal length	2,8mm	2,8mm	2,8mm	2.8-12 mm AutoFocus MotorZoom	2.8-12 mm AutoFocus MotorZoom	2.8-12 mm AutoFocus MotorZoom</

Model	1080p ECO+		
			
	SF-CV029-F4N1 (White) SF-CV029I-F4N1 (Gray)	SF-DM955VIB-F4N1	SF-CV788VIB-F4N1
Image Sensor Type	2Mpx High performance CMOS		
Effective pixel	1920 (H) × 1080 (V)		
Focal length	3.6mm	2.8-12mm	2.8-12mm
Field of view	83°	102°~32°	102°~32°
Video output	1 X BNC switchable HDTVI, HCDVI, AHD,CVBS		
Video resolution	1080p@25fps (1920x1080) 720p@50fps (1280x720)		
Day/Night	Day/Night, IR CUT filter		

Model	Series 8 PoC			Series 6 - HEVC		
						
	SF-HTVR8104AP-HEVC	SF-HTVR8208AP-HEVC	SF-HTVR8216AP-HEVC	SF-HTVR6104M-HEVC	SF-HTVR6104-HEVC	SF-HTVR6104A-HEVC
Video standard	HDTVI/HDCVI/AHD/CBVS/IP			HDTVI/HDCVI/AHD/CBVS/IP		
Video input	4ch BNC +2 IP (Extra) Up to 6MP Max 4ch IP exchange to Channel BNC Support Safire POC Camera	8ch BNC +4 IP (Extra) Up to 6MP Max 8ch IP exchange to Channel BNC Support Safire POC Camera	8ch BNC +4 IP (Extra) Up to 6MP Max 8ch IP exchange to Channel BNC Support Safire POC Camera	4ch		

Model	PoC Series 6		
			
	SF-HTVR6104AP-HEVC	SF-HTVR6208AP-HEVC	SF-HTVR6216AP-HEVC
Video standard	HDTVI/HDCVI/AHD/CBVS/IP		
Video input	4ch BNC +2 IP (Extra) Up to 6MP Max 4ch IP exchange to Channel BNC Support Safire POC Camera	8ch BNC +4 IP (Extra) Up to 6MP Max 8ch IP exchange to Channel BNC Support Safire POC Camera	16ch BNC +8 IP (Extra) Up to 6MP Max 16ch IP exchange to Channel BNC Support Safire POC Camera
Encoding resolution	4MP Lite@15FPS, 1080P@25FPS, 720P@60FPS	4MP Lite@15FPS, 1080P@25FPS, 720P@60FPS	4MP Lite@15FPS, 1080P@25FPS, 720P@60FPS
Video Compression	H265+/H264+/H265/H264		
Video outputs	HDMI(1080P)/VGA(1080P)/BNC Spot		
Audio inputs/outputs	1/1		
Alarm/Relay	4/1		
Video analysis	Intrusion detection/Line crossing/Audio exception		

Model	H.265+ Lite Series				
					
	SF-IPDM943WH-4 (White) SF-IPDM943WHG-4 (Grey)	SF-IPDM934H-4	SF-IPCV025WH-4	SF-IPDM834ZWAH-4	SF-IPDM855ZHW-4 (White) SF-IPDM855ZHWG-4 (Grey)
Image Sensor type	Hi-Performance CMOS				
Resolution	4MP@20FPS				
Video codec	H.265+/H.264+/H.265/H264				
Focal length	2,8mm				

Model	H.264+ Lite Series				
					
	SF-IPDM934-3-LITE	SF-IPDM943-3-LITE	SF-IPCV025-3-LITE	SF-IPDM855ZW-3-LITE	SF-IPDM832ZW-3-LITE
	Hi-Permonfance CMOS				
	3MP@20FPS				
	H.264+/H264				
Focal length	2,8mm	2,8mm	2,8mm	2.8-12 mm AutoFocus MotorZoom	2.8-12 mm AutoFocus MotorZoom
Field of view	105°	98°			

Model	IP Speed Dome Series					
						
	SF-IPSD6025UIWH-4	SF-IPSD7025UWH-2	SF-IPSD6625UIWH-2	SF-IPSD6525UAWH-2	SF-IPSD6025UIWH-2	SF-IPSD6015UIWH-2
Image Sensor Type	Hi-Permonfance CMOS Ultra Low Light	Hi-Permonfance CMOS	Hi-Permonfance CMOS Ultra Low Light	Hi-Permonfance CMOS	Hi-Permonfance CMOS Ultra Low Light	Hi-Permonfance CMOS Ultra Low Light
Effective pixel	4MP@25fps	2MP@30fps	2MP@25fps	2MP@30fps	2MP@25fps	2MP@25fps
Video codec	H.265+/H.264					

Model	NVR Series 6			
				
	SF-NVR6104-4K-VS2	SF-NVR6104-4K4P-VS2	SF-NVR6108-4K	SF-NVR6108-4K-VS2
Video IP input	4ch	4ch	8ch	8ch
Decoding resolution	8MP Max.			
Video Compresión	H.265+/H.264+/H.265/H.264			
Incoming Badwidth	40Mbps	40Mbps	80Mbps	80Mbps
Video outputs	1 HDMI (4K) 1 VGA Independent (1080p)			
Synchronous decoding	1-ch @ 8 MP or 4-ch @ 1080p			
Audio Input/Output	From MIC IP camera / 1-ch RCA			
Alarm Input / Relay	-	-	-	-
Video analysis	VCA, ANR			
POE Interface	-			

Model	NVR Series 6		
			
	SF-NVR6232A-4K	SF-NVR6432-4K	SF-NVR6432-4K16P
Video IP input	32ch		
Decoding resolution	8MP Max.		
Video Compresión	H.265+/H.264+/H.265/H.264		
Incoming Badwidth	256Mbps		
Video outputs	1 HDMI (4K) 1 VGA independent (1080p)		
Synchronous decoding	2 ch @ 4K, or 8-ch @ 1080p		
Audio Input/Output	From MIC IP camera / 1-ch RCA		
Alarm Input / Relay	4/1	16/4	16/4
Video analysis	VCA, ANR		
POE Interface	-	-	16 Ports up to 200W, 300m (Max.) PoE IEEE802.3af
Auxiliary interface	1 X RJ45 10/100/1000 Mbps 2x USB 2,0 1x USB 3,		

